

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number
WO 2004/057189 A1


- (51) International Patent Classification⁷: F04B 39/12, 39/00
- (21) International Application Number: PCT/KR2002/002403
- (22) International Filing Date: 20 December 2002 (20.12.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): LG ELECTRONICS INC. [KR/KR]; 20, Yido-Dong, Yong-dungpo-Gu, 150-010 Seoul (KR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HA, Jong-Hun [KR/KR]; Daedong Apt. 113-906, Sangnam-Dong, 641-777 Changwon, Gyeongsangnam-Do (KR). HA, Samchul [KR/KR]; Sapa Dongsung Apt.102-1201, Sapa-Dong, 641-775 Changwon, Gyeongsangnam-Do (KR). LEE, Won-Hack [KR/KR]; Gyeryong Apt. 844-801, Suri-Dong, 435-751 Gunpo, Gyeonggi-Do (KR).
- (74) Agent: PARK, Jang-Won; Jewoo Bldg. 5th Floor, 200, Nonhyun-Dong, Gangnam-Ku, 135-010 Seoul (KR).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: CHAMBER FOR COMPRESSOR AND COMPRESSOR USING THE SAME



(57) Abstract: A chamber (10) for a compressor is disclosed in which at least one portion has a multi-layer structure (11) and plates having the multi-layer structure are tightly attached to thereby reduce noise and vibration by virtue of mutual frictional force. Vibration energy is transformed to thermal energy according to friction and transmitted externally through the chamber (10) during the operation of the compressor. Thus, noise and vibration generated during the operation of the compressor can be considerably reduced.

WO 2004/057189 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.